

FOXY oxygen analyzer (5 ppm - 1000 ppm)

- Zirconium sensor (5 ppm - 1000 ppm)
- Ready to work in approx. 10 seconds
- Integrated pump
- 4,5 hours of battery runtime (4300 mAh)
- Diffusion-resistant measurement hose, probe and calibration certificate included
- Lightweight (300 g)
- 180° turnable display



RECOMMENDED FOR

Argon

DATA

Product number: 9501150
 Dimensions: 140 x 85 x 90 mm
 Weight: 0,3 kg

WS Stick oxygen analyzer (1 ppm - 1000 ppm)



- Optical sensor (1 ppm - 1000 ppm)
- Ready to work in 5 seconds
- Water and humidity resistant aluminium cabinet
- 10 hours of battery runtime (3000 mAh)
- Diffusion-resistant measurement hose, probe and calibration certificate included.
- Integrated bluetooth (class 1, 100 m coverage) for sending data
- 180° turnable display
- Integrated flashlight for welding inspection

RECOMMENDED FOR

All gases

DATA

Product number: 9503000
 Dimensions: Ø56 mm x 280 mm
 Weight: 0,5 kg

WS OXY I oxygen analyzer (5 ppm - 1000 ppm)

- Zirconium sensor (5 ppm - 1000 ppm)
- Color coded screen for easier readability
- 4 hours of battery runtime (3200 mAh)
- Can store welding data (*premium*)
- Diffusion-resistant measurement hose, probe and calibration certificate included
- Keyboard can be operated while wearing welding gloves



RECOMMENDED FOR

Argon

DATA

Product number: 9501000
 Dimensions: 225 x 105 x 45 mm
 Weight: 0,570 kg